

ppm-Tabelle für 1 - 5 Liter bei 5mA

(Elektrodenlänge 80 mm, Eintauchtiefe ca. 70 mm)

| ppm | 1 Liter Minuten | 2 Liter Minuten | 3 Liter Minuten | 4 Liter Minuten | 5 Liter Minuten |
|-----|--------------------|--------------------|--------------------|--------------------|--------------------|
| 10 | 30 | 60 | 90 | 120 | 150 |
| 20 | 60 | 120 | 180 | 240 | 300 |
| 25 | 75 | 150 | 225 | 300 | 375 |
| 30 | 90 | 180 | 270 | 360 | 450 |
| 40 | 120 | 240 | 360 | 480 | 600 |
| 50 | 150 | 300 | 450 | 600 | 750 |
| 60 | 180 | 360 | 540 | 720 | 900 |
| 70 | 210 | 420 | 630 | 840 | 1050 |
| 80 | 240 | 480 | 720 | 960 | 1200 |
| 90 | 270 | 540 | 810 | 1080 | 1350 |
| 100 | 300 | 600 | 900 | 1200 | 1500 |

ppm-Tabelle für 1 - 5 Liter bei 10mA

(Elektrodenlänge 150 mm, Eintauchtiefe ca. 140 mm)

| ppm | 1 Liter Minuten | 2 Liter Minuten | 3 Liter Minuten | 4 Liter Minuten | 5 Liter Minuten |
|-----|--------------------|--------------------|--------------------|--------------------|--------------------|
| 10 | 15 | 30 | 45 | 60 | 75 |
| 20 | 30 | 60 | 90 | 120 | 150 |
| 25 | 38 | 75 | 113 | 150 | 188 |
| 30 | 45 | 90 | 135 | 180 | 225 |
| 40 | 60 | 120 | 180 | 240 | 300 |
| 50 | 75 | 150 | 225 | 300 | 375 |
| 60 | 90 | 180 | 270 | 360 | 450 |
| 70 | 105 | 210 | 315 | 420 | 525 |
| 80 | 120 | 240 | 360 | 480 | 600 |
| 90 | 135 | 270 | 405 | 540 | 675 |
| 100 | 150 | 300 | 450 | 600 | 750 |